
TVB-5706

Telecamera termica TruVision, 640x512, ottica 15 mm

Panoramica

Le termocamere TruVision offrono una soluzione per applicazioni di rilevamento perimetrale e monitoraggio di alta sicurezza in condizioni di illuminazione difficili. \La telecamera termica è dotata di funzioni di analisi integrate come l'intrusione in un'area, l'attraversamento di una linea, l'ingresso in una regione e il rilevamento dell'uscita dalla regione. Include anche il monitoraggio della temperatura per infrastrutture critiche. \Le termocamere TruVision possono essere utilizzate in combinazione con una varietà di piattaforme di registrazione TruVision e UltraView, nonché con qualsiasi piattaforma di terze parti che utilizza la connettività Onvif o CGI.



Caratteristiche standard

- Compressione H.265
- Sensore immagine non raffreddato
- Rilevazione a lunga portata
- Grado di protezione IP66 per installazioni in esterno
- Supporto 50fps
- Analisi video per la protezione perimetrale
- Doppia uscita video IP e analogica (PAL)
- Compatibile con PoE+
- Slot per memorie SD per la registrazione locale

TVB-5706

Telecamera termica TruVision, 640x512, ottica 15 mm


Dati tecnici

Camera	
Sensor Size	1/3"
Total Pixels (H x V)	640 x 512
Image sensor	Vanadium Oxide Uncooled Focal Plane Arrays
MRAD	1.13 mrad
Minimum focal distance	2.5m
Maximum detection range	1,353m (vehicle) / 441m (human)
Maximum recognition range	338m (vehicle) / 110m (human)
Maximum identification range	169m (vehicle) / 55m (human)
Colors	14 pseudo colors adjustable
Lighting performance	
Wide dynamic range (WDR)	True WDR
WDR	120dB
Digital Noise Reduction	3D NR
Encoding	
Video Streams	3
Video Compression Main Stream	H.264, H.265, MJPEG, MPEG4
Video Compression Sub Stream	H.264, H.265, M-JPEG, MPEG-4
Max. Resolution @ fps	640 x 512 @ 50fps
Lens	
Focal length	15 mm
F-stop	1.0
Lens Type	Fixed
Network	
Supported Network Protocols	802.1x, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, Qos, RTP, RTSP, SMTP, SNMP, TCP, UDP
Supported Video Standards	CGI, ONVIF, PSIA
Audio	
Audio In	1 Mic in/Line in interface, line input: 2-2.4V[p-p]; output impedance: 1KO, ±10%
Audio Out	1 Audio output interface, line level, impedance: 600O
Audio Compression	G.711A, G.711U, G.722, G.726
Alarm I/O	
Alarm Outputs	2
Alarm Inputs	2
Storage	
Max Storage Capacity	Up to 128GB
Local Storage Support	Yes
Local Storage Type	Micro SD/SDHC/SDXC
Video intelligence	
Basic Alarm Detection	Motion, Privacy Masking
Video Analytics	Audio exception, Cross line, Intrusion detection, Region entrance detection, Region exit detection
General	
Technology	Analog, IP
Display Modes	Mirror
OSD	Text Overlay
Video Output	BNC Composite PAL 1.0 Vp-p @ 75 Ohm
Video Standard	PAL
Electrical	
Power consumption	8W
Operating voltage	24VAC 12VDC PoE+ (802.3at)
Physical	
Form Factor	Bullet
Physical dimensions	Ø 115.8 × 327.8
Net weight	2 kg 4.41lb
Colour	Grey

Environmental	
Operating temperature	-40°C to 65°C -40°F to 140°F
Relative humidity	90% or less, no condensation
Environment	Indoor / Outdoor
IP-rating	IP66
Standards & regulation	
Compliancy	CE, cUL, REACH, RoHS, UL, WEEE

Come ordinare

Codice prodotto	Descrizione
TVB-5706	Telecamera termica TruVision, 640x512, ottica 15 mm



Quale società aperta alle innovazioni UTC Fire & Security si riserva il diritto di variare le caratteristiche tecniche dei prodotti senza preavviso. Per avere le specifiche tecniche aggiornate è possibile visitare on line UTC Fire & Security al sito www.utcfssecurityproducts.it oppure contattare il vs. rivenditore UTC Fire & Security
TVB-5706-2018-02-1 08:54:19 Released :11-JAN-18

United Technologies
Climate | Controls | Security